

DESCRIPTION



LUSTER is design to work on a wide variety of substrates and in many different maintenance methods. It performs exceptional well on linoleum, decorative vinyl and stone surfaces. Provides exceptional clarity with minimal gloss – ideal for maintaining a natural substrate appearance or for locations where high gloss is not preferred.

FEATURES AND BENEFITS

- ✓Provides terrific long-term protection for all of your walking surfaces.
- ✓Low gloss characteristics help to hide blemishes, cut lines, traffic lanes and dirt embedment to provide an even, clean look over a longer period of time.

INDUSTRY STANDARDS AND APPROVALS

LEED v4 Points Contribution **LEED Points**
 Health Product Declaration Up to 2 points.
 (HPD)* .

Using this product may help contribute to LEED certification of projects in the category shown above. Points are awarded based on contributions of all project materials.

SURFACE PREPARATION

All POLICRETE products require a surface preparation. The surface should be grinded, repair and be flat. Read all installation instructions thoroughly before applying the products(see TDS and SDS).

- ✓Blockade areas to be stripped or finished.
- ✓Floors will be slippery until dry.
- ✓Strip floor using.

PRODUCT APPLICATION

Application

Do not dilute the product.

Coating

Using a clean mop, apply a maximum of 3 medium coats of LUSTER.
 After 24 hours, additional coats may be applied until desired gloss is achieved.
 Allow 30-40 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time.
 Allow finish to cure for 24 hours before burnishing or applying extra coats.
 Apply no more than 3 coats in a 24-hour period.

Maintenance

Dust mop or sweep.

Recoating

Dust mop or sweep.
 Clean the floor w
 Blockade area and apply 1-2 uniform coats of fi-

nish using a clean mop.
 Allow finish to cure for 24 hours before burnishing.

Shelf Life and Storage

Two (2) years in factory delivered unopened pouches. Once stabilized, 24 hours.
 Keep awayfrom extreme heat, cold and moisture. Maintain at a proper storage temperature of 50-90°F.Keep out of direct sunlight and a way from fire hazards.

Repairs and Maintenance

Do Not clean floor with solvents or solvent based cleaners. Contact POLICRETE for specific cleaner recommendations.

PROTECTION

- Protect the installation from foot traffic, rain and freezing for 24 hours.
- Protect the installed LUSTER from contamination, excessive heat and extended sun exposure until the finish flooring is installed.

Coverage: 2000-2500 sqf/gal.

PACKGING

LUSTER is packaged in a 1 gallon and 5 gallon.

TECHNICAL DATA

COLOR/Form	Milky White, Liquid
pH	8.5
Scent	Ammonia

LEGAL NOTICE

The technical data and any other printed information furnished by POLICRETE are true and accurate to the best of our knowledge. LUSTER conforms to in house quality control procedures and should be considered free of defects. The data provided is believed to be reliable and is offered solely for evaluation. The use of this product is beyond the control of the seller, therefore the buyer assumes all risks of use and handling whether done in a matter that is in accordance with the provided posted directions or not. POLICRETE makes no warranty; expressed or implied, of its products and shall not be liable for indirect or consequential damage in any event.
ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED POLICRETE WARRANTIES.
 Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLE SHOULD HAVE BEEN DISCOVERED.**